



DATE: October 3, 2017

COLLIN COUNTY
LIZ GRAY

Christopher Simon
972.313.5537

700A WILMETH RD
MCKINNEY, TEXAS 75069-8231

One (1) New Caterpillar Model: 299D XHP Compact Construction Equipment with all standard equipment in addition to the additional specifications listed below:

SELL PRICE	\$132,863
Quote thru NIPA Contract	

WARRANTY

Standard Warranty: 12 Month/Unlimited Hours Total Machine
 Extended Warranty: 60 months / 4,000 hour PT&H

MACHINE SPECIFICATIONS

DESCRIPTION	REF.#
299D2 XHP COMPACT TRACK LOADER	435-9000
SELF LEVEL	435-9238
RIDE CONTROL	422-3445
DOOR, CAB, POLYCARBONATE	345-6260
RADIO, AM/FM, BLUETOOTH	345-6180
PACKAGE, LAND MANAGEMENT (LM2)	494-5809
RUBBER BELT, 2 SPD, TF IDLERS	454-6062
TRACK,RUBBER,400MM(15.7IN)BLCK	389-7673
LIGHTS, LED	495-1671
SEAT BELT, 2"	258-4095
FAN,COOLING, DEMAND, REVERSING	457-2835
QUICK COUPLER, MANUAL	345-4910
SERIALIZED TECHNICAL MEDIA KIT	421-8926
HEATER, ENGINE COOLANT, 120V	345-3556
PRODUCT LINK, CELLULAR PL240	441-4818
BUCKET, MP, 78", BOCE	426-6548
GUARD, MANUAL COUPLER	231-2578
COLD PLANER, PC412B	381-8370
MANUALS	INCLUDED
5 YEAR SUBSCRIPTION TO VISION LINK	INCLUDED
BEACON LIGHT WITH GUARD	INCLUDED

***Optional Items not Included in Quoted Price

Forks - \$1,000

Industrial Grapple Bucket - \$3,950

STANDARD EQUIPMENT

POWERTRAIN

Cat C3.8 Turbo Aftercooled Diesel Engine

- Gross Horsepower per SAE J1349

110 hp (82 kW) @ 2400 RPM

- EPA Tier 4 Final and EU Stage IV

Certified with Aftertreatment

- Electric Fuel Priming Pump

- Air Inlet Heater Starting Aid

- Liquid Cooled, Direct Injection

Air Cleaner, Dual Element, Radial Seal

S-O-S Sampling Valve, Hydraulic Oil

Filter, Cartridge Type, Hydraulic

Filters, Cartridge Type, Fuel

and Water Separator

Radiator/Hydraulic Oil

Cooler (side-by-side)

Spring Applied, Hydraulically Released,

Wet Multi Disc Parking Brakes

Hydrostatic Transmission

UNDERCARRIAGE

Steel Imbed Rubber Track 15.7 in (400mm)

Triple Flange Idler - front and rear

Suspension - Independent Torsion Axle(4)

Two Speed Travel with Ride Control

HYDRAULICS

HYDRAULICS, XHP

- High Flow: 40 gpm (150 lpm) max

- High Flow Pressure: 4061 psi

28000 kPa max

- Continuous Flow

- Hydraulics, Proportional

- Worktool Harness

CONTROLS:

Electro/Hydraulic Implement Control, RH

Electro/Hydraulic Hydrostatic

Transmission Control, LH

STARTERS, BATTERIES, & ALTERNATORS

1000 CCA Heavy Duty Battery w/Disconnect

ELECTRICAL

12 Volt Electrical System

100 Ampere Alternator

Ignition Key Start / Stop / Aux Switch

Lights:

- Gauge Backlighting

- Two Rear Tail Lights

- Two Rear Halogen Working Lights

- Two Adjustable Front Halogen Lights

- Dome Light

Backup Alarm

Electrical Outlet, Beacon

OPERATOR ENVIRONMENT

Operator Warning System Indicators:

- Air Filter Restriction

- Alternator Output

- Armrest Raised / Operator Out of Seat

- Hydrostatic Transmission Disables

- Parking Brake Engages

ROPS, Cab, Enclosed (C3), Tilt Up:

- Air Conditioner incl Heater/Defroster

- Engine Coolant Temperature
- Engine Oil Pressure
- Air Inlet Heater Activation
- Hydraulic Filter Restriction
- Hydraulic Oil Temperature
- Park Brake Engages
- Engine Emission System

Gauges: DEF Level, Fuel Level,
Hour Meter and Tachometer

Storage compartment with netting

Seat, Comfort, Air Suspension, Cloth,
Heat

- High Back heated seat with recline
- Lumbar support
- Fully adjustable Seat Mounted
Controls

Ergonomic Contoured Armrest

Control Interlock System, when Operator
Leaves Seat or Armrest Raised :

- Hydraulic System Disables

- Side Windows
- Cup Holder

FOPS, Level I

Top and Rear Windows

Deluxe Headliner

Floormat

Interior Rear View Mirror

12V Electric Socket

Horn

Hand (Dial) & Foot Throttle, Electro

Dual Direction Electronic Self Level -
(Raise and lower)

Work Tool Return to Dig

Work Tool Positioner

Electronic Snubbing (Lift)

Advanced LCD Display

- Full color 5 inch LCD screen
- Advanced Anti-theft Security System
with 50 user code capability
- Rear View Camera

FRAMES

Lift Linkage, Vertical Path

Chassis, One Piece Welded

Machine Tie Down Points (4)

Belly Pan Cleanout

Support, Lift Arm

Cast Rear Bumper

Ventilated Rear Door with Integrated
Sealing

OTHER STANDARD EQUIPMENT

Engine Enclosure - Lockable

Extended Life Antifreeze (-37C, -34F)

Coupler, Mechanical

Hydraulic Oil Level Sight Gauge

Radiator Coolant Level Sight Gauge

Radiator Expansion Bottle

Cat Tough Guard Hose

Heavy Duty Flat Faced Quick Disconnects
with Integrated Pressure Release

Split D-Ring to Route Work Tool Hoses

Along Side of Left Lift Arm

Variable Speed Hydraulic Cooling Fan

Per SAE J818-2007 and EN 474-3:2006 and
ISO 14397-1:2007

Rated Operating Capacity :

At 50% Tipping Load

- 4725 lb (2143 kg)

At 35% Tipping Load

- 3308 lb (1500 kg)