



DATE: September 15, 2017
 QUOTE #:198796-01

COLLIN COUNTY
 LIZ GRAY

Christopher Simon
 972.313.5537

700A WILMETH RD
 MCKINNEY, TEXAS 75069-8231

One (1) New Caterpillar Model: CW34 Paving and Compaction with all standard equipment in addition to the additional specifications listed below:

SELL PRICE	\$217,950
Quote thru BuyBoard Contract #515-16	

WARRANTY

Standard Warranty: 12 Month/Unlimited Hours Total Machine
 Extended Warranty: 60 months / 5,000 hour premier warranty
Buy Back Terms: 60 months or 5,000 hours: \$66,000

MACHINE SPECIFICATIONS

DESCRIPTION	REF.#
CW34 PNEUMATIC COMPACTOR	445-5711
ENGINE, TIER 4F/STAGE 4	443-8810
FRAME, STANDARD MACHINE	445-5707
AIR CONDITIONER	364-6761
CAB, ROPS W/HEATER & DEFROSTER, SEAT BELT	359-7793
SEAT, STD CLOTH	364-6749
CONTROL, PREMIUM	457-1622
PRODUCT LINK, CELLULAR PL641 WITH 5 YEARS SERVICE	454-5454
TIRES, STD	359-7789
OIL, HYD, FACTORY FILLED	364-8437
BALLAST, 44,000 LB	471-9322
LIGHTS, HALOGEN, CAB	367-3674
MIRRORS, EXTERNAL	364-6763
SUN SCREEN	351-3438
ROPS	359-7792
MAPPING, GNSS	440-5393
COCOA MAT W/SCRAPER	388-7112
SPRAY, EMULSION	359-7790
AM / FM RADIO WITH WEATHERBAND	INCLUDED

STANDARD EQUIPMENT

POWERTRAIN

Cat C4.4 ACERT Engine
Dual element cyclonic air cleaner
Fuel filter / water separator
Ultra clean fuel filter with integrated
prime pump
Fuel reducing, automotive style,
variable speed engine control

Automatic idle shutdown
Dual braking system (service & parking)
Continuously variable hydrostatic
transmission with seamless shifting
3 Speed ranges
Auto speed control (ASC) for lower noise
and fuel consumption

ELECTRICAL

24-volt electric starting
100 - amp alternator
Two CAT Maintenance Free Batteries
Roading lights - turn signals and low
beam forward facing lights
Rear backup light and stop indication

lamps
Halogen working lights - bumper mounted
(2 front-facing and 2 rear-facing)
Backup alarm and forward warning horn
Product Link Ready

OPERATOR ENVIRONMENT

Side to side sliding and plus/minus 90
degree rotating operator station
Machine and operating functions are
integrated into 4" LCD display
Fore/Aft adjustable suspension seat
Oversized RH arm rest

3" wide belt
Vandalism protection
Power assisted steering
Tilt able steering column
Rubber floor mat

FLUIDS

Premixed 50% concentration of Extended
Life Coolant with freeze protection

to -37C (-35F)

OTHER STANDARD EQUIPMENT

Locking fiberglass engine enclosure
All wheel oscillation - front and rear
Front wheel vertical equalizing
suspension
Single pump, triple filtration
pressurized water system
Dedicated system for each tire
Intermittent adjustable spray on/off

time
Water Capacity
Self adjusting, retractable, nylon tire
scrapering system
Manual brake release
Lockable fuel fill
Transport tie-down and lift points
High ambient capable (49 deg C)