



DATE: October 3, 2017

**COLLIN COUNTY**  
LIZ GRAY

**Christopher Simon**  
972.313.5537

700A WILMETH RD  
MCKINNEY, TEXAS 75069-8231

**One (1) New Caterpillar Model: 299D XHP Compact Construction Equipment with all standard equipment in addition to the additional specifications listed below:**

SELL PRICE	\$137,780
Quote thru NIPA Contract	

**WARRANTY**

Standard Warranty: 12 Month/Unlimited Hours Total Machine  
 Extended Warranty: 60 months / 4,000 hour PT&H

**MACHINE SPECIFICATIONS**

DESCRIPTION	REF.#
299D2 XHP COMPACT TRACK LOADER	435-9000
SELF LEVEL	435-9238
RIDE CONTROL	422-3445
DOOR, CAB, POLYCARBONATE	345-6260
RADIO, AM/FM, BLUETOOTH	345-6180
PACKAGE, LAND MANAGEMENT (LM2)	494-5809
RUBBER BELT, 2 SPD, TF IDLERS	454-6062
TRACK,RUBBER,400MM(15.7IN)BLCK	389-7673
LIGHTS, LED	495-1671
SEAT BELT, 2"	258-4095
FAN,COOLING, DEMAND, REVERSING	457-2835
QUICK COUPLER, MANUAL	345-4910
SERIALIZED TECHNICAL MEDIA KIT	421-8926
HEATER, ENGINE COOLANT, 120V	345-3556
PRODUCT LINK, CELLULAR PL240	441-4818
GUARD, MANUAL COUPLER	231-2578
BUCKET, MP, 78" BOCE	426-6548
MULCHER, HM415C, XHP	475-2790
5 YEARS OF VISION LINK	INCLUDED
BEACON LIGHT WITH GUARD	INCLUDED

\*\*\*Optional Items not Included in Quoted Price

Forks - \$1,000

Industrial Grapple Bucket - \$3,950

## STANDARD EQUIPMENT

---

### POWERTRAIN

Cat C3.8 Turbo Aftercooled Diesel Engine

- Gross Horsepower per SAE J1349  
110 hp (82 kW) @ 2400 RPM
- EPA Tier 4 Final and EU Stage IV  
Certified with Aftertreatment
- Electric Fuel Priming Pump
- Air Inlet Heater Starting Aid
- Liquid Cooled, Direct Injection

Air Cleaner, Dual Element, Radial Seal

S-O-S Sampling Valve, Hydraulic Oil  
Filter, Cartridge Type, Hydraulic  
Filters, Cartridge Type, Fuel  
and Water Separator  
Radiator/Hydraulic Oil  
Cooler (side-by-side)  
Spring Applied, Hydraulically Released,  
Wet Multi Disc Parking Brakes  
Hydrostatic Transmission

### UNDERCARRIAGE

Steel Imbed Rubber Track 15.7 in (400mm)

Triple Flange Idler - front and rear

Suspension - Independent Torsion Axle(4)

Two Speed Travel with Ride Control

### HYDRAULICS

HYDRAULICS, XHP

- High Flow: 40 gpm (150 lpm) max
- High Flow Pressure: 4061 psi  
28000 kPa max
- Continuous Flow
- Hydraulics, Proportional

- Worktool Harness

CONTROLS:

Electro/Hydraulic Implement Control, RH  
Electro/Hydraulic Hydrostatic  
Transmission Control, LH

### STARTERS, BATTERIES, & ALTERNATORS

1000 CCA Heavy Duty Battery w/Disconnect

### ELECTRICAL

12 Volt Electrical System

100 Ampere Alternator

Ignition Key Start / Stop / Aux Switch

Lights:

- Gauge Backlighting
- Two Rear Tail Lights

- Two Rear Halogen Working Lights  
- Two Adjustable Front Halogen Lights  
- Dome Light  
Backup Alarm  
Electrical Outlet, Beacon

### OPERATOR ENVIRONMENT

Operator Warning System Indicators:

- Hydrostatic Transmission Disables

- Air Filter Restriction
- Alternator Output
- Armrest Raised / Operator Out of Seat
- Engine Coolant Temperature
- Engine Oil Pressure
- Air Inlet Heater Activation
- Hydraulic Filter Restriction
- Hydraulic Oil Temperature
- Park Brake Engages
- Engine Emission System

Gauges: DEF Level, Fuel Level,  
Hour Meter and Tachometer

Storage compartment with netting

Seat, Comfort, Air Suspension, Cloth,  
Heat

- High Back heated seat with recline
- Lumbar support
- Fully adjustable Seat Mounted  
Controls

Ergonomic Contoured Armrest

Control Interlock System, when Operator  
Leaves Seat or Armrest Raised :

- Hydraulic System Disables

- Parking Brake Engages

ROPS, Cab, Enclosed (C3), Tilt Up:

- Air Conditioner incl Heater/Defroster
- Side Windows
- Cup Holder

FOPS, Level I

Top and Rear Windows

Deluxe Headliner

Floor mat

Interior Rear View Mirror

12V Electric Socket

Horn

Hand (Dial) & Foot Throttle, Electro

Dual Direction Electronic Self Level -  
(Raise and lower)

Work Tool Return to Dig

Work Tool Positioner

Electronic Snubbing (Lift)

Advanced LCD Display

- Full color 5 inch LCD screen
- Advanced Anti-theft Security System  
with 50 user code capability
- Rear View Camera

## FRAMES

Lift Linkage, Vertical Path

Chassis, One Piece Welded

Machine Tie Down Points (4)

Belly Pan Cleanout

Support, Lift Arm

Cast Rear Bumper

Ventilated Rear Door with Integrated  
Sealing

## OTHER STANDARD EQUIPMENT

Engine Enclosure - Lockable

Extended Life Antifreeze (-37C, -34F)

Coupler, Mechanical

Hydraulic Oil Level Sight Gauge

Radiator Coolant Level Sight Gauge

Radiator Expansion Bottle

Cat Tough Guard Hose

Heavy Duty Flat Faced Quick Disconnects  
with Integrated Pressure Release

Split D-Ring to Route Work Tool Hoses

Along Side of Left Lift Arm

Variable Speed Hydraulic Cooling Fan

Per SAE J818-2007 and EN 474-3:2006 and  
ISO 14397-1:2007

Rated Operating Capacity :

At 50% Tipping Load

- 4725 lb (2143 kg)

At 35% Tipping Load

- 3308 lb (1500 kg)